

SHOWA

DURACoil 546

Polyurethane foam coating over engineered DURACoil liner reinforced with HPPE

FEATURES

- 13 gauge seamless knit liner with HPPE
- Foamed polyurethane palm coating for good grip & aeration
- EN 388:2016: Cut Level C
- ANSI/ISEA 105-16: A3
- Lightweight, flexible liner with elastic knitted wrist
- Breathable open back design

BENEFITS

- Ultra-comfortable multi-purpose glove with durable cut resistant properties for precision handling.
- Increased cut resistance performance due to engineered fibre wrapping technology
- PU foamed coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- Breathable back of hand to reduce perspiration and keep hands dry
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Cost-efficient gloves that can be laundered and re-used
- Seamless knit designed to prevent irritation

INDUSTRY



Aerospace



Automotive



Engineering



Glass



Manufacturing



Mechanical



Metallurgy



Railways



Warehousing & Distribution

IDEAL APPLICATIONS

- Dry & oily parts assembly
- Bottling
- Glass & window fixing
- Canning
- White goods
- Automotive repairs & maintenance
- Mechanical engineering
- Mounting & dismantling



MATERIAL

- HPPE
- Polyester

COATING

- Polyurethane



NORMS



SHOWA

DURACoil 546



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- 6/S
- 7/M
- 8/L
- 9/XL
- 10/XXL



COLOUR

- Grey



THICKNESS

- 1.3mm



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
541



MATERIAL
HPPE
COATING
Polyurethane
CATEGORY
Cut

SHOWA
DURACOIL 546W



MATERIAL
Engineered yarn
COATING
Polyurethane
CATEGORY
Cut

SHOWA
DURACoil 546X



MATERIAL
Engineered yarn
COATING
Uncoated
CATEGORY
Cut

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved