

Gate Valve Lockout



Product Highlights

Risk Type: Mechanical Risk

Dimensions: 5.2 in Dia

Part Number: 65561

Overview

Gate valve lockout devices deny access and cover the valve handle. This device's unique knockout center fits OS&Y or "rising stem" valves.

- Device is made of extremely rugged injection-molded polypropylene for superior impact and chemical resistance
- Supplied with English, Spanish and French danger labels
- Cover the valve handle with the gate valve lockout device and apply a personal padlock and lockout tag to ensure employee safety
- Accepts padlock shackles up to 3/8 in. in diameter

Specifications

Key Characteristics	<u>Catalog Page #</u>	211
	Product Number	65561
	UPC	754473655617
	UOM	Each
	Brand Name	Brady®
	<u>Country of Origin</u>	China
Dimensions	Dimensions	5.2 in Dia
	Diameter	5.2 in
	Valve Wheel Diameter Range	2.5 to 5 in
	Rising Stem Knockout Hole Diameter	1.75 in
	Lockout Height	2 in
	Lockout Width	7.28 in
Material Characteristics	<u>Material Number</u>	LOTO-7 (View Technical Data Sheet)
	Lockout Material	Polypropylene
	Lockout Color	Red
	Service Temperature Range °F	-40°F to 302°F
	Minimum Service Temperature °F	-40 °F

	Maximum Service Temperature °F	302 °F
Product Features	Gate Valve Lockout Type	Hinged
	Maximum Number of Padlocks	1
	Risk Type	Mechanical Risk
Compatibility	Maximum Shackle Diameter	0.375 in
	Text Legend	DANGER LOCKED OUT DO NOT REMOVE
Preprinted Information	Language	English, French, Spanish
	UNSPSC	39121909
Compliance	National Stock Number (NSN)	5120015007631