

4-Legged Ball Valve Lockout



Product Highlights

Risk Type: Mechanical Risk

Valve Size Range: 0.5 to 2.5 in

Part Number: BS07A-RD

Overview

Patented design and ultra-tough polypropylene material make these devices the best choice to assuredly lock out your ball valves.

- 4-Legged Ball Valve Lockout devices lock out pipes 1/2" to 2-1/2" in diameter and can lock valves OPEN on pipes from 1/2" to 1-1/4" in diameter
- Ultra-tough polypropylene resists temperatures from 0° to 175°F (-18° to 79°C)
- Equipping your employees with the proper lockout tools and warning devices can save lives, reduce lost employee time, and cut insurance costs
- Brady® is a world leader in lockout/tagout products and services offering industry expertise and a broad range of durable, easy-to-use lockout devices

Specifications

Key Characteristics	<u>Catalog Page #</u>	212
	Product Number	45341
	UPC	754473453411
	UOM	Each
	Trade Name	Brady®
	Brand Name	Brady®
	<u>Country of Origin</u>	United States of America
Dimensions	Dimensions	4.07 in H x 3.05 in W x 5.31 in D
	Height	4.07 in
	Width	3.05 in
	Depth	5.31 in
	Valve Size Range	0.5 to 2.5 in
	Pipe Diameter Range	1/2 to 2-1/2 in
Material Characteristics	<u>Material Number</u>	LOTO-22 (View Technical Data Sheet)
	Lockout Material	Polypropylene
	Lockout Color	Red
	Service Temperature Range °F	-40 to 302 °F
	Minimum Service Temperature °F	-40 °F

	Maximum Service Temperature °F	302 °F
	Conductivity	Conductive
Product Features	Ball Valve Lockout Type	Fits over Valve
	Maximum Number of Padlocks	2
	Open or Closed Valve?	Both
	Risk Type	Mechanical Risk
Compatibility	Maximum Shackle Diameter	0.313 in
	Maximum Handle Thickness	0.5 in
	Maximum Handle Width	1 in
	Minimum Pipe Diameter	0.5 in
	Maximum Pipe Diameter	2.5 in
Compliance	UNSPSC	39121909