

4-Legged Ball Valve Lockout



Product Highlights

Risk Type: Mechanical Risk

Valve Size Range: 2 to 8 in

Part Number: BS08A-RD

Overview

Patented design and ultra-tough polypropylene material make these devices the best choice to assuredly lock out your ball valves.

- Large Ball Valve Lockout Device locks out pipes 2 in. to 8 in. in diameter
- Ultra-tough polypropylene resists temperatures from 0° to 175°F (-18° to 79°C)
- Equipping your employees with the proper lockout tools and warning devices can save lives, reduce lost employee time, and cut insurance costs
- Brady® is a world leader in lockout/tagout products and services offering industry expertise and a broad range of durable, easy-to-use lockout devices

Specifications

Key Characteristics	<u>Catalog Page #</u>	212
	Product Number	45345
	UPC	754473453459
	UOM	Each
	Brand Name	Brady®
	<u>Country of Origin</u>	United States of America
Dimensions	Dimensions	8.666 in H x 4.44 in W x 12 in D
	Height	8.666 in
	Width	4.44 in
	Depth	12 in
	Valve Size Range	2 to 8 in
	Pipe Diameter Range	2 to 8 in
Material Characteristics	<u>Material Number</u>	LOTO-22 (View Technical Data Sheet)
	Lockout Material	Polypropylene
	Lockout Color	Red
	Service Temperature Range °F	-40°F to 302 °F

	Minimum Service Temperature °F	-40 °F
	Maximum Service Temperature °F	302 °F
	Conductivity	Conductive
Product Features	Ball Valve Lockout Type	Fits over Valve
	Maximum Number of Padlocks	2
	Open or Closed Valve?	Closed
	Risk Type	Mechanical Risk
Compatibility	Maximum Shackle Diameter	0.313 in
	Maximum Handle Thickness	1 in
	Maximum Handle Width	1.75 in
	Minimum Pipe Diameter	2 in
	Maximum Pipe Diameter	8 in
Compliance	UNSPSC	39121909