

Standard Ball Valve Lockout

Product Highlights

Risk Type: Mechanical

Risk Valve Size Range: 1.25 to 3 in

Dimensions: 4.8 in H x 5 in W x 7.5 in D

Part Number: 65669



Overview

The easy-to-use, single piece design of Ball Valve Lockouts from Brady® makes them the perfect tool for securing your valve handles in the off position.

- Locks out ball valve sizes from 1.25 in. to 3 in. (fits standard 9/32 in. lock shackle diameters)
- Made of powder-coated steel for superior rust resistance
- Equipping your employees with the proper lockout tools and warning devices can save lives, reduce lost employee time, and cut insurance costs
- Brady® is a world leader in lockout/tagout products and services offering industry expertise and a broad range of durable, easy-to-use lockout devices

Specifications

| | | |
|--------------------------|--------------------------|---|
| Key Characteristics | <u>Catalog Page #</u> | 212 |
| | Product Number | 65669 |
| | UPC | 754473656690 |
| | UOM | Each |
| | Brand Name | Brady® |
| | <u>Country of Origin</u> | China |
| Dimensions | Dimensions | 4.8 in H x 5 in W x 7.5 in D |
| | Height | 4.8 in |
| | Width | 5 in |
| | Depth | 7.5 in |
| | Valve Size Range | 1.25 to 3 in |
| | Pipe Diameter Range | 1-1/4 to 3 in |
| Material Characteristics | <u>Material Number</u> | LOTO-23 (View Technical Data Sheet) |
| | Coating Material | Powder Coated |
| | Lockout Material | Steel |
| | Lockout Color | Red |

| | | |
|------------------|--|------------------|
| | Service Temperature Range °F | -20°F to 200°F |
| | Minimum Service Temperature °F | -20 °F |
| | Maximum Service Temperature °F | 200 °F |
| | Conductivity | Conductive |
| Product Features | Ball Valve Lockout Type | Fits over Handle |
| | Maximum Number of Padlocks | 1 |
| | Open or Closed Valve? | Closed |
| | Risk Type | Mechanical Risk |
| Compatibility | Maximum Shackle Diameter | 0.282 in |
| | Maximum Handle Thickness | 0.43 in |
| | Maximum Handle Width | 2.1 in |
| | Minimum Pipe Diameter | 1.25 in |
| | Maximum Pipe Diameter | 3 in |
| Compliance | UNSPSC | 39121909 |