

Standard Ball Valve Lockout



Product Highlights

Risk Type: Mechanical Risk

Valve Size Range: 1.25 to 3 in

Dimensions: 4.8 in H x 5 in W x 7.5 in D

Part Number: 65693

Overview

The easy-to-use, single piece design of Ball Valve Lockouts from Brady® makes them the perfect tool for securing your valve handles in the off position.

- Locks out ball valve sizes from 1.25 in. to 3 in. (fits standard 9/32 in. lock shackle diameters)
- Made of powder-coated steel for superior rust resistance
- Equipping your employees with the proper lockout tools and warning devices can save lives, reduce lost employee time, and cut insurance costs
- Brady® is a world leader in lockout/tagout products and services offering industry expertise and a broad range of durable, easy-to-use lockout devices

Specifications

Key Characteristics	<u>Catalog Page #</u>	212
	Product Number	65693
	UPC	754473656935
	UOM	Each
	Brand Name	Brady®
	<u>Country of Origin</u>	China
Dimensions	Dimensions	4.8 in H x 5 in W x 7.5 in D
	Height	4.8 in
	Width	5 in
	Depth	7.5 in
	Valve Size Range	1.25 to 3 in
	Pipe Diameter Range	1-1/4 to 3 in

Material Characteristics	<u>Material Number</u>	LOTO-23 (View Technical Data Sheet)
	Coating Material	Powder Coated
	Lockout Material	Steel
	Lockout Color	Red
	Service Temperature Range °F	-40 to 347 ?
	Minimum Service Temperature °F	-20 °F
	Maximum Service Temperature °F	200 °F
	Product Features	Ball Valve Lockout Type
Maximum Number of Padlocks		1
Open or Closed Valve?		Closed
Risk Type		Mechanical Risk
Compatibility	Maximum Shackle Diameter	0.375 in
	Maximum Handle Thickness	0.43 in
	Maximum Handle Width	2.1 in
	Minimum Pipe Diameter	1.25 in
	Maximum Pipe Diameter	3 in
Compliance	<u>UNSPSC</u>	