


Cert No :		44528 - 2		Date	28-Dec-20
CERTIFICATE OF CONFORMITY					
ULTIMATE PLUS SUPPLY CO. LTD 219/178, MOO5, SOI, CHAIPITAK2 NGAMWONGWAN ROAD, THUNGSONGHONG TEL : +662 954 9641 FAX : +662 9549642 BANGKOK, THAILAND				Order Ref	44528
				Customer Ref	PO NO:20-227
Rope Lanyard According to EN354:2010					
ID Nos	Product Reference	Description of product	Qty	Remarks	
A205221 / 5551 to A205221 / 5570	LO147150CDD	Double lanyard in Braided rope Ø 10,5 mm, 2 sewn loop ends. One AM002 and two AM022. Length 1,5m	20	Breaking Strength 5000 lbs	
Brand: DELTA PLUS					
 Quality Engineer					
We Certify that the product listed above have been produced and tested in accordance with the requirements of the above mentioned Standard					
Validity: 1 Year from the date of first use					
<u>DIRECTIONS FOR USE</u>					
Please follow all the instructions and recommendations provided with the Notice of Use. Visual examination before each use: stitched, straps and buckles. All should be in perfect state. Ensure that rescue operation could eventually be carried out safely. Personal attribution of PPE to one user. Check the compatibility of all the elements constituting the fall arrest system, connectors, lanyards, absorbers, winding devices, etc. During use, protect the PPE from sharp edges, welding discharges, heat sources, chemical aggressions. This PPE is to be used by properly trained and competent personnel. Anchorage point situated above user, Resistance > 1500 kgs. No modification must be made on the PPE. Change the equipment in case of any doubt or in case of a fall.					
QSP10/R3		ISSUE07		20.11.2014	