

# Technical specs

**EX120\_** - EX120

**Name:**

POSITIONING BELT - 2 ANCHORAGE POINTS

**Size:**

Adjustable

**Colour:**

Black / Orange-coloured



CE 0082

**Description :**

Positioning belt with thermoformed back. 2 lateral anchorage points for work positioning. 1 adjustment loop. Sponge back lining.

**Materials:**

Belt : Sponge lining.

Weight : 0,4 kg.

**Strong points:**

Easy to positioning.

Light.

Side attachment point.

**Instructions for use:**

The test methods described in the standards do not represent actual usage conditions. It is therefore important to study each work situation and that each user is fully trained in different techniques in order to know the limits of the various devices. This lanyard can be an element or connection component in fall arrest personal protection systems (restraint systems, work positioning systems (EN358), fall arrest systems (EN353-1, EN353-2, EN355, EN360), access by means of ropes and rescue systems) systems. It can also be an anchorage device (EN795). This product is inseparable from a comprehensive fall protection system (EN363), whose function is to minimize the risk of body injury from falls. The fall arrest harness (EN361) is the only body grip to be allowed for use with a fall arrest system. It must be connected to the fall arrest system by connectors (EN362).

WARNING: It is recommended to assign each user a belt.

WARNING:

THE LANYARD IS NOT A GRIP BODY DEVICE, ONLY THE HARNESS IS RESERVED FOR THIS FUNCTION (EN361).

THE LANYARD SHOULD NOT BE USED AS A FALL ARREST BY ITSELF. In case of a fall risk, it is necessary to supplement this system with a collective or personal restraint or protection device against falls from a height (EN363).

THE ADJUSTABLE LANYARD IS NOT A GRIP BODY DEVICE, ONLY THE HARNESS IS RESERVED FOR THIS FUNCTION (EN361). THE ADJUSTABLE LANYARD MUST NOT BE USED FOR THE PREVENTION NOR FOR THE ARREST OF FALLS. The adjustable lanyard can not be used connected to a work support belt (EN358) by connectors (EN362). SPECIAL NOTE: It is recommended to assign each user a lanyard.

The vertical clearance is the stopping distance H + additional safety distance of 1 m. The distance H measured from the initial position to the final position (user's balance after the fall arrest).

**Limits to use:**

Do not use this equipment out of its usage specifications defined in the instructions above. Be careful about pendular effect during equipment use.

Textile products or those containing textile elements (harnesses, belts, shock absorbers etc...): maximum life of 10 years in storage (from date of manufacture), 7 years after the first use. The shelf life is given as an indication.

Metal products and mechanical products (self retracting fall arrest device, sliding, work on ropes, anchors etc. ...) : Maximum duration of 20 years from the date of manufacture (including storage and use). The shelf life is given as an indication.



**DELTA PLUS GROUP**

La Peyrolière - B.P. 140 - 84405 APT Cedex - France  
www.deltaplus.fr



# Technical specs

## EX120\_ - EX120

The following factors can cause it to vary greatly:

- Non-compliance with the manufacturer's instructions for transport, storage and use
- "Aggressive" work environment: marine atmosphere, chemicals, extreme temperatures, sharp edges...
- Particularly intensive use
- Shock or significant constraint
- Disregard for the product item's history. Warning: these factors can cause damage invisible to the naked eye.

Warning: certain extreme conditions can shorten the shelf life by a few days. If in doubt, always remove the product for it to undergo either:

- a review
- destruction

The shelf life is not a substitute for periodic verification (minimum annually) which will assess the condition of the product. This equipment should be used in work environments with minimum temperatures of -20°C / maximum of +50°C.

### FEATURE OUTSIDE OF STANDARD:

This PPE has been tested with a mass constraint 40% higher than the standard requirements (at 140 kg)

### Instructions for storage:

During transport and storage:

- keep the product in its packaging
- keep the product away from any sharp, abrasive, objects etc#
- Keep the product away from sunlight, heat, flames, hot metal, oil, petroleum products, harsh chemicals, acids, dyes, solvents, sharp edges and structures of small diameter. These items can affect the performance of the fall arrest device.

After use, store the product in its packaging in a cool, dry, ventilated area.

### Instructions for cleaning / maintenance:

Clean with soap and water, wipe with a cloth and hang in a ventilated area to dry naturally away from any direct fire or source of heat, even for items that got wet during use.

Do not use bleach, harsh detergents, solvents, gasoline or colouring, these substances can affect the performance of the fall arrest device.

Clean the strap with a soft detergent only.

The metal parts are wiped with a cloth soaked in vaseline oil.

### Performances :

Compliance with the essential requirements of Directive 89/686/EEC, in particular in terms of design, ergonomics and safety. Meets with requirements and test standards EN363, EN364, EN365, EN358.

Strap: tensile strength > 22 kN.

Tested at 140 kg according to EN358, see product marking.



**DELTA PLUS GROUP**

La Peyrolière - B.P. 140 - 84405 APT Cedex - France  
www.deltaplus.fr

