

# ALLSAFE (FZE)



# أوول سيف (م.م.ح)

P.O. Box : 7968, Saif Zone, Sharjah, U.A.E.  
Tel. : +9716- 5572285, Fax : +9716 - 5572286  
E- mail : sales@allsafe.ae, info@allsafe.ae  
Website : www.allsafe.ae

ص.ب : ٧٩٦٨ ، سيف زون ، الشارقة - ا.ع.م  
تليفون : +٩٧١٦-٥٥٧٢٢٨٥ ، فاكس : +٩٧١٦-٥٥٧٢٢٨٦  
البريد الإلكتروني sales@allsafe.ae  
www.allsafe.ae الإنترنت

Certificate No : 21451 - 7 Date 6-Apr-15

## CERTIFICATE OF CONFORMITY

ULTIMATE PLUS SUPPLY CO. LTD 219/178, MOO5, SOI, CHAIPITAK2 NGAMWONGWAN ROAD, THUNGSONGHONG TEL : +662 954 9641 FAX : +662 9549642 BANGKOK, THAILAND	Order No	21451
	Customer Ref.	PO:15-019

### STRAP SELF-RETRACTABLE FALL ARRESTER According to EN360 - CE APPROVED

ID Nos	Product Ref	Description of product	Qty	Remarks
F1405780192, F1405780183, F1405780181, F1405780119, F1405780179, F1405780180, F1405780184, F1405780118, F1405780191, F1405780186	AN153T	Self retractable fall arrester with galvanised steel cable with integrated energy absorber. ABS case. Fall indicator. Inertia locking system. Length: 10 m. 1 connector AM016.	10	Breaking Strength >12kN. and tested at 150Kg according to EN360

Zack PETER

We Certify that the Fall arrester listed above have been produced and tested in accordance with the requirements of the above mentioned Standards.  
Validity:- 6 Months from the date of first use

**Genuine Product Policy:** To verify the authenticity of our product, please email at [genuine@allsafe.ae](mailto:genuine@allsafe.ae)

#### USAGE LIMITS AND GENERAL INSTRUCTIONS

Metal products and mechanical products duration of 20 years from the date of manufacture (including storage and use). The shelf life is given as an indication. The following factors can cause it to vary greatly:

- Non-compliance with the manufacturer's instructions for transport, storage and use
- "Aggressive" work environment: marine atmosphere, chemicals, extreme temperatures, sharp edges...
- Particularly intensive use and Shock or significant constraint
- Disregard for the product item's history
- Warning: these factors can cause damage invisible to the naked eye
- Warning: certain extreme conditions can shorten the shelf life by a few days
- If in doubt, always remove the product for it to undergo either a review or destruction
- The shelf life is not a substitute for periodic verification (minimum annually) which will assess the condition of the product.
- This equipment should be used in work environments with minimum temperatures of -32°C / maximum of +50°C



QSP10/R3

ISSUE07

20.11.2014

Manufacturers of :

Webbing Slings Round Slings Cargo Lashings Full Body Harnesses

