

## Optional accessories



## Model GX-3R



1 Heat-resistant case	Unit case for hot environment. uses a safety pin.	Part No. 4777 4259 40
2 Leather case	Unit case for protection against dirt. uses the clip on the unit.	Part No. 4777 4257 00
3 Belt clip	Allows the product to be attached to a belt or pocket.	Part No. 4777 9202 40
4 Arm/Ankle belt	Belt for securing the unit to your arm or ankle.	Part No. 4777 9293 30
5 Protective film	Protects the display.	Part No. 4777 9296 50
6 Manual suction unit	External manual pump. Draws in at greater flow rates than electric pump.	Part No. 4777 9301 10
7 Charging cradle	Cradle for recharging the unit. Cradles can be interconnected.	Part No. 4777 21
8 Five-unit AC adaptor	One AC adapter recharges up to five units. *Recharging times remain unchanged.	Part No. 4777 9319 80
9 Calibration adaptor	Adapter for connecting the gas sampling bag to the main unit for calibration.	Part No. 4777 9311 00
10 Data management program	Software for viewing and managing measurement data.	Part No. 9811 0870 60

## Pump unit RP-3R

An external electric pump. Allows use for suction sampling.



### Specifications

Model	RP-3R
Suction flow rate	High mode: Approx. 0.5 L/min Low mode: Approx. 0.35 L/min
Battery	AA alkaline battery × 1
Continuous operating time	High mode: Approx. 10 hours Low mode: Approx. 16 hours
Temperature range	-20°C~+50°C (at a constant condition)
Humidity range	0~95%RH (non-condensing)
Explosion-proof class	Inherently safe explosion-proof construction TIIS Ex ia IIC T4 Ga ATEX II1G Ex ia IIC T4 Ga IECEx Ex ia IIC T4 Ga
Structure	Drip-proof and dust-proof performances compliant to IP67 level
Dimensions / Weight	Approx. 82mm (W) × 96mm (H) × 29mm (D) / Approx. 120g
Optional accessories	Float-type gas sampling tube Filters (set of 10) Meshes (set of 10)

\* Cannot be connected to other models GX-2009, GX-3R Pro and others.

## Docking station SDM-3R

Allows the user to perform a simplified pre-work check (bump test) and gas calibration automatically.



### Specifications

Model	SDM-3R
Power supply	100 to 240 V AC ±10%, 50/60 Hz
Suction flow rate	Approx. 0.25 L/min
Temperature range	0~40°C (at a constant condition)
Humidity range	0~95%RH (non-condensing)
Dimensions / Weight	Approx. 130mm (W) × 110mm (H) × 250mm (D) / Approx. 810g
Optional accessories	Connecting fixture, wall-mounting fixture, exhaust tube

## Also consider the high-spec [GX-3R Pro] model!

- Up to 5 gases can be detected**  
Detects carbon dioxide and sulfur dioxide in addition to combustible gases, O<sub>2</sub>, H<sub>2</sub>S, and CO.
- Connected with Bluetooth**  
Allows connection to a smartphone. Use the dedicated app iOS, Android to send alarm notifications by email.
- Runs on either dry cell or rechargeable batteries**  
Unit system for easy replacement.
- Easy-to-read full-dot display**  
Supports a total of 11 different languages.

## Model GX-3R Pro



\* For details, see the GX-3R Pro catalog.